



Material Safety Data Sheet

EpoxAmite 100 Resin and 102 Medium Hardener

Date Of Preparation: September 11, 2013

MSDS No.3031
Revision: 0005

Section 1 - Chemical Product and Company Identification

Product/Chemical Name: EpoxAmite 100 Resin
Other Designations: Formulated Epoxy
General Use: Laminating, Adhesive and Casting Resin
Manufacturer: Smooth-On Inc., 2000 St. John St., Easton PA 18042
Phone (610) 252-5800, FAX (610) 252-6200
Emergency Contact: Chem-Tel
Domestic 800-255-3924
International 813-248-0585

Section 2- Hazards Identification

Not hazardous according to United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200), the Canadian Workplace Hazardous Materials Information System (WHMIS) and Council directive 1999/45/EC and its subsequent amendments.

HMIS	
H	1
F	1
R	0

Section 3 - Composition / Information on Ingredients


No hazardous ingredients

Section 4 - First Aid Measures

Inhalation: Remove to fresh air: if breathing is labored seek medical attention.
Eye Contact: Flush with water for 15 minutes: seek medical attention
Skin Contact: Remove with soap and water: if redness or rash develops seek medical attention: Launder contaminated clothing before reuse.
Ingestion: seek medical attention
After first aid, get appropriate in-plant, paramedic, or community medical support.

Section 5 - Fire-Fighting Measures

Flash Point: >485 °F (252 °C)
Flash Point Method: PMCC
Flammability Classification: Non-Flammable
Extinguishing Media: Foam, Dry Chemical, and Carbon Dioxide
Unusual Fire or Explosion Hazards: None
Hazardous Combustion Products: Oxides of Nitrogen and Carbon, Acids and Aldehydes when burned.
Fire-Fighting Instructions: Do not release runoff from fire control methods to sewers or waterways.
Fire-Fighting Equipment: Because fire may produce toxic thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full-face piece operated in pressure-demand or positive-pressure mode.



Section 6 - Accidental Release Measures

Spill /Leak Procedures

Containment: Dike and contain for later disposal. Do not release into sewers or waterways.

Cleanup: Scrape up excess.

Regulatory Requirements: Follow applicable OSHA regulations (29 CFR 1910.120).

Section 7 - Handling and Storage

Handling Precautions: Avoid prolonged or repeated skin contact. Use good general housekeeping procedures.

Storage Requirements: Store in Closed containers. Use only with adequate ventilation.

Section 8 - Exposure Controls / Personal Protection

Respiratory Protection: Follow OSHA respirator regulations 29 CFR 1910.134 and European Standard EN 149; wear an MSHA/NIOSH or European Standard EN149 approved respirator.

Protective Clothing/Equipment: Wear chemically protective gloves to prevent prolonged or repeated skin contact. Wear protective eyeglasses or chemical safety goggles, per OSHA eye- and face-protection regulations 29 CFR 1910.133 and European Standard EN166. Contact lenses are not eye protective devices. Appropriate eye protection must be worn instead of, or in conjunction with contact lenses.



Comments: Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics

Section 9 - Physical and Chemical Properties

Physical State: Liquid

Appearance and Odor: Water-White to Yellow; Faint Epoxy Odor

Vapor Pressure: None (Polymeric Resin)

Vapor Density (Air=1): None (Polymeric Resin)

Specific Gravity (H₂O=1, at 4 °C): 1.14

Water Solubility: negligible

Boiling Point: None (Polymeric Resin)

Freezing/Melting Point: None (Polymeric Resin)

Evaporation Rate: None (Polymeric Resin)

Viscosity: 10 poise

Section 10 - Stability and Reactivity

Stability: This product is stable at room temperature in closed containers under normal storage and handling conditions.

Polymerization: Hazardous polymerization cannot occur.

Chemical Incompatibilities: Strong oxidizing agents, strong Lewis or mineral acids.

Conditions to Avoid: Mixing with Amines under uncontrolled conditions.

Hazardous Decomposition Products: Thermal oxidative decomposition of Epoxy Resin EEW-190 can produce: Oxides of Nitrogen and Carbon, Acids and Aldehydes when burned.

Section 11- Toxicological Information

Eye Effects: Irritation
Skin Effects: Irritation

Carcinogenicity: None
Mutagenicity: None Determined
Teratogenicity: None Determined

Section 12 - Ecological Information

None Determined

Section 13 - Disposal Considerations

Disposal: Contact your supplier or a licensed contractor for detailed recommendations. Follow applicable Federal, state, and local regulations.

Section 14 - Transport Information

DOT
Not Regulated

IATA
Not Regulated

IMDG
Not Regulated

Section 15 - Regulatory Information

EPA Regulations: This material is not considered a hazardous material.

RCRA Hazardous Waste Number: Not listed (40 CFR 261.33): None

RCRA Hazardous Waste Classification (40 CFR 261): Not classified

CERCLA Hazardous Substance (40 CFR 302.4) unlisted specific per RCRA, Sec. 3001; CWA, Sec. 311 (b)(4); CWA, Sec. 307(a), CAA, Sec. 112

CERCLA Reportable Quantity (RQ), None

SARA 311/312 Codes: None

SARA Toxic Chemical (40 CFR 372.65): None

SARA EHS (Extremely Hazardous Substance) (40 CFR 355): Not listed,

TSCA Inventory Status (40CFR710): All components of this formula are on the TSCA inventory

California Proposition 65: This product does not intentionally contain any chemicals which have been identified by the state of California to cause cancer, birth defects or other reproductive harm.

16 - Other Information

Disclaimer: The information contained in this MSDS is considered accurate as of the version date. However, no warranty is expressed or implied regarding the accuracy of the data. Since the use of this product is not within the control of Smooth-On Inc., it is the user's obligation to determine the suitability of the product for its intended application and assumes all risk and liability for its safe use.

This Material Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200), the Canadian Workplace Hazardous Materials Information System (WHMIS), and European Union Directive 1907/2006/EEC (REACH). Hazard symbols and risk phrases are based on maximum listed concentration of each hazardous ingredient. Unlisted ingredients are not "hazardous" per the OSHA Hazard Communication Standard (29 CFR 1910.1200), the Canadian Workplace Hazardous Materials Information System (WHMIS) or the European Union (EU/EEC) directive 1907/2006/EEC and are considered trade secrets under US Federal Law (29CFR and 40CFR), Canadian Law (Health Canada Legislation), and European Union Directives



Material Safety Data Sheet

EpoxAmite 100 Resin and 102 Medium Hardener

MSDS No.3031
Revision: 0005

Date Of Preparation: September 11, 2013

Section 1 - Chemical Product and Company Identification

Product/Chemical Name: 102 Medium Hardener
Other Designations: Curing Agent, Epoxy
General Use: Laminating, Adhesive and Casting Resin
Manufacturer: Smooth-On Inc., 2000 St. John St., Easton PA 18042
Phone (610) 252-5800, FAX (610) 252-6200
Emergency Contact: Chem-Tel
Domestic 800-255-3924
International 813-248-0585

Section 2- Hazards Identification

Hazard Designation:



Xi: Irritant



N: Dangerous for the environment

HMIS	
H	2
F	1
R	0

Risk Phrases pertaining to particular dangers

- R22:** Harmful if swallowed.
- R36:** Irritating to eyes.
- R37:** Irritating to respiratory system.
- R38:** Irritating to skin.

Classified according to Articles 6 & of Directive 1999/45/EC

Section 3 - Hazards Identification

Component	ACGIH TWA	Exposure Limits OSHA PEL	Hazard Designation	Weight Percent (%)
Teta, reaction products with propylene oxide CAS Number: 26950-63-0 EINECS Number: 500-055-5	None Established	None Established	Not Classified	50-55
Polyoxypropylene triamine CAS Number: 39423-51-3 EINECS Number: 500-105-6	None Established	None Established	Not Classified	20-25
Triethylenetetramine CAS Number: 112-24-3 EINECS Number: 203-950-6	None Established	None Established	C	15-20

Section 4 - First Aid Measures

Inhalation: Remove to fresh air; if breathing is labored seek medical attention.

Eye Contact: Flush with water for 15 minutes; seek medical attention

Skin Contact: remove with soap and water: if redness or rash develops seek medical attention:
Launder contaminated clothing before reuse.

Ingestion: do not induce vomiting; seek medical attention

After first aid, get appropriate in-plant, paramedic, or community medical support.

Section 5 - Fire-Fighting Measures

EpoxAmit 102 Hardener Flash Point: 347°F (175°C)

Flammability Classification: Combustible Liquid, Class III

Extinguishing Media: Foam, Dry Chemical, and Carbon Dioxide

Unusual Fire or Explosion Hazards: None

Hazardous Combustion Products: May generate Ammonia gas, Oxides of Nitrogen and Carbon when burned

Fire-Fighting Instructions: Do not release runoff from fire control methods to sewers or waterways.

Fire-Fighting Equipment: Because fire may produce toxic thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure-demand or positive-pressure mode.



Section 6 - Accidental Release Measures

Spill /Leak Procedures

Containment: Dike and contain for later disposal. Do not release into sewers or waterways.

Cleanup: Cover minor spills with sodium bisulfate to neutralize and reduce vapors. Spray with water. Place in metal containers for recovery or disposal. Clean-up personnel must be equipped with self-contained breathing apparatus and butyl rubber protective clothing.

Regulatory Requirements: Follow applicable OSHA regulations (29 CFR 1910.120).

Section 7 - Handling and Storage

Handling Precautions: Avoid prolonged or repeated eye and skin contact. Avoid breathing vapors and use only with adequate ventilation. Use good general housekeeping procedures.

Storage Requirements: Keep away from oxidizers. Store in Closed containers. Use only with adequate ventilation.

Section 8 - Exposure Controls / Personal Protection

Respiratory Protection: Follow OSHA respirator regulations 29 CFR 1910.134 and European Standards EN 141, 143 and 371; wear an MSHA/NIOSH or European Standards EN 141, 143 and 371 approved respirators. *Warning! Air-purifying respirators do not protect workers in oxygen-deficient atmospheres.* If respirators are used, OSHA requires a written respiratory protection program that includes at least: medical certification, training, fit-testing, periodic environmental monitoring, maintenance, inspection, cleaning, and convenient, sanitary storage areas.

Protective Clothing/Equipment: Wear chemically protective gloves, boots, and aprons to prevent prolonged or repeated skin contact. Wear protective eyeglasses or chemical safety goggles, per OSHA eye- and face-protection regulations 29 CFR 1910.133 and European Standard EN166. Contact lenses are not eye protective devices. Appropriate eye protection must be worn instead of, or in conjunction with contact lenses.



Comments: Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics.

Section 9 - Physical and Chemical Properties

<p>Physical State: Appearance and Odor: Light Amber liquid, ammonia odor Vapor Pressure: <1 mm/Hg @ 21 °C Vapor Density (Air=1): >1 Specific Gravity (H₂O=1, at 4 °C): 1.01</p>	<p>Water Solubility: No Data Boiling Point: No Data Freezing/Melting Point: No Data Evaporation Rate: No Data pH: No Data</p>
---	--

Section 10 - Stability and Reactivity

Stability: This material is stable at room temperature in closed containers under normal storage and handling conditions.

Polymerization: Hazardous polymerization cannot occur.

Chemical Incompatibilities: Strong oxidizing agents, strong Lewis or mineral acids.

Conditions to Avoid: Mixing with epoxies under uncontrolled conditions.

Hazardous Decomposition Products: Thermal oxidative decomposition of can produce: Ammonia gas, Oxides of Nitrogen and Carbon when burned. Combustion of product under oxygen-starved conditions can be expected to produce numerous toxic products including nitriles, cyanic acid, isocyanates, cyanogens, nitrosamines, amides, and carbamates.

Section 11- Toxicological Information

<p>Eye Effects: Irritant Skin Effects: Irritant Acute Toxicity Effects Data: Oral LD50 (rat): 500 mg/kg Dermal LD50 (rabbit): >1000 mg/kg</p>	<p>Mutagenicity: No Data Teratogenicity: No Data</p>
---	---

Section 12 - Ecological Information

None Determined

Section 13 - Disposal Considerations

Disposal: Contact your supplier or a licensed contractor for detailed recommendations. Follow applicable Federal, state, and local regulations.

Section 14 - Transport Information

DOT	IATA	IMDG
Not Regulated	<p>Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Polyoxypropylene triamine and Triethylenetetramine) UN #: 3082 Hazard Class: 9 Label: Miscellaneous Marine Pollutant</p>	<p>Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Polyoxypropylene triamine and Triethylenetetramine) UN #: 3082 Hazard Class: 9 Label: Miscellaneous Marine Pollutant</p>

Section 15 - Regulatory Information

EPA REGULATIONS:

SARA 312 (40 CFR #70) Hazard Classification: Acute Health Hazard, Chronic Health Hazard

SARA Title III Section 313 (40 CFR 372): None

TSCA Inventory Status (40CFR710): All components of this formula are on the TSCA inventory

California Proposition 65: This product does not intentionally contain any chemicals which have been identified by the state of California to cause cancer, birth defects or other reproductive harm.



CANADIAN REGULATIONS:

WHMIS Identification: D2A, D2B

CDSL/NDL (Canadian Domestic Substance List/Non Domestic Substance List): **Listed on CDSL**



Labeling according to EEC Directive

Risk Phrases	Symbol(s) Required for EU Label	Safety Phrases
R22: Harmful if swallowed. R36: Irritating to eyes R37: Irritating to respiratory system. R38: Irritating to skin	 Xi: Irritant  N: Dangerous for the environment	S1/2: Keep locked up and out of reach of children S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice S36/37/38: Wear suitable protective clothing, gloves, and eye face/protection. S45: In case of an accident or if you feel sick, seek medical attention. S61: Avoid release to the environment.

16 - Other Information

Disclaimer: The information contained in this MSDS is considered accurate as of the version date. However, no warranty is expressed or implied regarding the accuracy of the data. Since the use of this product is not within the control of Smooth-On Inc., it is the user's obligation to determine the suitability of the product for its intended application and assumes all risk and liability for its safe use.

This Material Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200), the Canadian Workplace Hazardous Materials Information System (WHMIS), and European Union Directive 1907/2006/EEC (REACH). Hazard symbols and risk phrases are based on maximum listed concentration of each hazardous ingredient. Unlisted ingredients are not "hazardous" per the OSHA Hazard Communication Standard (29 CFR 1910.1200), the Canadian Workplace Hazardous Materials Information System (WHMIS) or the European Union (EU/EEC) directive 1907/2006/EEC and are considered trade secrets under US Federal Law (29CFR and 40CFR), Canadian Law (Health Canada Legislation), and European Union Directives.