

1. Chemical Product and Company Identification

Polytek Development Corp., 55 Hilton St., Easton, PA 18042, 610/559-8620
 Product Name: **EASYFLO 60, 95, 120 & CLEAR PART A**
 Chemical Family: Methylene bis(phenylisocyanate)

2. Hazardous Constituents

Hazardous Ingredient/CAS #	Exposure Limits
Methylene bis(phenylisocyanate) (MDI), CAS# 101-68-8, and other isomers	ACGIH TLV 0.005 ppm TWA OSHA PEL 0.02 ppm (Ceiling)
Proprietary plasticizer	None established

3. Health Hazards

PRIMARY ROUTE(S) OF ENTRY: Skin and eye contact
 EYE: Causes eye irritation.
 SKIN: Exposure may cause skin irritation, staining, or sensitization. Skin contact may cause respiratory sensitization.
 INGESTION: Single oral dose toxicity is low. No harmful effects anticipated from ingesting small amounts incidental to normal handling.
 INHALATION: At room temp., vapors are minimal. Vapors or aerosols (e.g., generated during heating or spraying) may cause respiratory irritation. May cause respiratory sensitization in susceptible individuals. For individuals sensitized to MDI, exposure may result in allergic respiratory reactions (e.g., coughing, difficulty breathing).
 CHRONIC EFFECTS: Repeated or prolonged overexposure to MDI may cause respiratory and dermal sensitization. Long-term overexposure to MDI may result in impaired lung function.
 CARCINOGENICITY: Not designated as a carcinogen by NTP, IARC, or OSHA. Rats exposed to MDI aerosol for their lifetime developed lung tumors.

4. First Aid Measures

EYE CONTACT: Flush with water immediately for 15 minutes. Seek medical attention.
 SKIN CONTACT: Wash with soap and plenty of water (preferably warm water).
 INHALATION: Remove to fresh air. Treat symptoms. Seek medical attention.
 INGESTION: Seek medical attention. Do not induce vomiting unless so directed by a physician.

5. Fire Fighting Measures

FLASH POINT: > 300 °F (estimated)
 EXTINGUISHING MEDIA: Carbon dioxide, dry chemical, foams, or water spray.
 HAZARDOUS COMBUSTION PRODUCTS: May include MDI vapor, nitrogen oxides, isocyanates, carbon monoxide, carbon dioxide, and unidentified toxic and irritating compounds.
 OTHER INFORMATION: Firefighters wear SCBA and full-body protective suit. Solid stream of water into hot product may cause violent steam generation or eruption. Dense smoke is formed when product burns. Use water to cool hot containers.

6. Accidental Release Measures

Clear non-emergency personnel from the area. Extinguish sources of ignition. Contain spill to minimize environmental contamination. Absorb spilled material with an inert absorbent. Collect

and containerize material. Do not seal containers of spill residue since carbon dioxide is generated upon contact with moisture and dangerous pressure buildup can occur. Neutralize contaminated floor area with a mixture of water (90%), ammonia (3-8%) and detergent (2%).

7. Handling and Storage

HANDLING: Avoid breathing vapor. Use in well ventilated area. Avoid contact with eyes, skin and clothing. Do not eat, drink or smoke in work area. Wash hands after handling. See Section 8.
 STORAGE: Store indoors at temperatures >55°F and <95°F. Store in original, unopened container. Protect from atmospheric moisture and water, since MDI reacts with water to form CO₂ leading to potentially dangerous pressure build up in sealed containers.

8. Exposure Controls/Personal Protection

ENGINEERING CONTROLS: Provide general and/or local exhaust to maintain airborne concentrations below exposure limits (see Section 1 for exposure limits).
 PERSONAL PROTECTIVE EQUIPMENT: Wear eye protection (e.g., chemical splash goggles), protective clothing and impermeable gloves (e.g., nitrile or butyl rubber).
 RESPIRATORY PROTECTION: In the absence of good ventilation, use respirator equipped with organic vapor cartridges and HEPA filters or air-supplied respirator. In emergencies, use SCBA.

9. Physical Characteristics

APPEARANCE: Clear yellow liquid	VAPOR PRESS.: .0007 mmHg @ 20°C (est.)
ODOR: Mild acrid odor	SPECIFIC GRAVITY: 1.2 @ 25°C
SOLUBILITY IN WATER: Insoluble, forms CO ₂	BOILING POINT: No data
pH: Not applicable	VISCOSITY: <150 cP

10. Stability and Reactivity

CONDITIONS TO AVOID: Moisture and temp's <55 °F and >95 °F to ensure product integrity.
 INCOMPATIBILITY WITH OTHER MATERIALS: Avoid contact with water, acids, bases, alcohols, strong oxidizers, and some metals (e.g., aluminum, brass, copper). Reaction with water generates carbon dioxide, and results in heat and pressure buildup in closed systems.
 HAZARDOUS DECOMPOSITION PRODUCTS: Possibly isocyanate vapor, carbon monoxide, nitrogen oxides, and traces of hydrogen cyanide.

11. Regulatory and Other Information

COMMUNITY RIGHT-TO-KNOW: This product contains the following Section 313 ingredient:

<u>Ingredient</u>	<u>CAS #</u>	<u>Weight %</u>
Methylene bis(phenylisocyanate)	101-68-8	<60

DISPOSAL: Upon disposal, this product is not a RCRA hazardous waste (per 40 CFR 261). Upon exposure to moisture, product forms an inert, non-hazardous solid.

TRANSPORT: Not a hazardous material for shipping in U.S., per 49 CFR Part 171.

HMIS RATING: Health=2*; Flammability=1; Reactivity=1; PPE=C

EMERGENCY SHIPPING INFORMATION: Call CHEMTREC, 800/424-9300.

MSDS INDICATOR: Minor format changes.

DISCLAIMER: The information contained herein is considered accurate; however, Polytek makes no warranty regarding the accuracy of the information. The user must determine the suitability of the product for the intended use and accepts all risk and liability associated with that use.