



Materials Safety Data Sheet
Aluminum Blackener

I PRODUCT IDENTIFICATION

TRADE NAME (AS LABELED): JAX CHEMICAL ALUMINUM BLACKENER
CHEMICAL NAMES, COMMON NAMES: NONE
SYNONYMS: NONE
MANUFACTURER'S NAME: JAX Chemical Company, Inc.
ADDRESS: 78-11 267th Street, Floral Park, New York 11004
BUSINESS PHONE: 718-347-0057

II HAZARDOUS INGREDIENTS

| CHEMICAL NAME | CAS # | % w/w | EXPOSURE LIMITS IN AIR | |
|----------------|-----------|-------|------------------------|---------------------------|
| | | | TLV ACGIH | PEL OSHA |
| Selenious Acid | 7783-00-8 | > 1.0 | 0.2 mg/m ³ | 0.2 mg(Se)/m ³ |

THE REMAINING 99 to 100% INGREDIENTS ARE NON-HAZARDOUS

III PHYSICAL PROPERTIES

VAPOR DENSITY: NO DATA
SPECIFIC GRAVITY: 1.02
SOLUBILITY IN WATER: SOLUBLE
VAPOR PRESSURE, mm Hg @ 20 C: NO DATA
APPEARANCE & COLOR: CLEAR LIQUID
EVAPORATION RATE (WATER = 1): SIMILAR TO WATER
MELTING POINT or RANGE: LESS THAN 32° F
BOILING POINT: GREATER THAN 212° F
pH: 2.2

HOW TO DETECT THIS SUBSTANCE (warning properties): At room temperature this product is a clear liquid with no odor. No unusual warning properties.

IV FIRE and EXPLOSION

THIS PRODUCT IS NON-FLAMMABLE AND NON-COMBUSTIBLE

FLASH POINT, F (method): N/A
AUTOIGNITION TEMPERATURE, F: N/A
FLAMMABLE LIMITS in air by volume, %: lower N/A upper N/A
FIRE EXTINGUISHING MATERIALS:
water spray: OK carbon dioxide: OK foam: OK
dry chemical: OK halon: OK other:

SPECIAL FIRE FIGHTING PROCEDURES: If involved in fire, use water spray.
Fire Fighters must use Self Contained Breathing Apparatus.

UNUSUAL FIRE & EXPLOSION HAZARDS: Product may decompose at high temperatures to form toxic gases.

V HEALTH HAZARD INFORMATION

SYMPTOMS OF OVER EXPOSURE by route of exposure:
INHALATION: Upper respiratory irritation. Metallic taste. Headache.
CONTACT WITH SKIN or EYES: Irritation and/or reddening and to skin and eyes.
Change in skin pigmentation.

