



Material Safety Data Sheet

SO-Flex

MSDS No. 625

Date Of Preparation: November 6, 2007

Revision: 0010

Section 1 - Chemical Product and Company Identification

Product/Chemical Name: SO-Flex (formerly PMC-724 Part C)

General Use: Polyurethane Elastomer

Manufacturer: Smooth-On Inc., 2000 St. John St., Easton PA 18042

Phone (610) 252-5800, FAX (610) 252-6200

Emergency Contact: Chem-Tel

Domestic 800-255-3924

International 813-248-0585

Section 2 - Composition / Information on Ingredients

OSHA Hazard Communication Standard 29 CFR1910.1200:

| Component | CAS Number | ACGIH TWA | Exposure Limits OSHA PEL | Weight Percent (%) |
|-----------------------------|------------|------------------------|--------------------------|--------------------|
| Butyl benzyl phthalate | 85-68-7 | None Established | None Established | 99-99.7 |
| Phenylmercuric neodecanoate | 26545-49-3 | 0.01 mg/m ³ | 0.01 mg/m ³ | 0.3 |

Section 3 - Hazards Identification

Potential Health Effects

Primary Entry Routes: Dermal

Target Organs: pancreas, liver, thyroid and eyes.

Acute Effects

Inhalation: Vapors, which are not significant unless heated or sprayed can cause irritation to respiratory tract.

Eye: May cause irritation, redness, tearing.

Skin: Contact will cause irritation and reddening swelling.

Ingestion: Effects are unknown.

Carcinogenicity: IARC, NTP, and OSHA do not list any components of this product as a carcinogen.

Medical Conditions Aggravated by Long-Term Exposure: Pre-existing skin disorders.

Chronic Effects of Overexposure:

This product contains an organo-mercury catalyst below the reportable level required by OSHA 1910.1200; however, due to the chronic toxicity of organo-mercury compounds careful handling of this product is required.

| HMIS | |
|------|---|
| H | 2 |
| F | 0 |
| R | 0 |

Section 4 - First Aid Measures

Inhalation: Remove source(s) of contamination and move victim to fresh air.

Eye Contact: Flush eyes with plenty of water. If irritation persists, seek medical attention.

Skin Contact: In case of skin contact, wash thoroughly with soap and water; remove contaminated clothing and launder before reuse; seek medical attention if rash develops.

Ingestion: Do not induce vomiting unless instructed by a physician. Contact physician immediately

After first aid, get appropriate in-plant, paramedic, or community medical support.

Section 5 - Fire-Fighting Measures

Flash Point: >300 °F (150°C)

Flash Point Method: COC

Flammability Classification: Non-Flammable

Extinguishing Media: Water Fog, Dry Chemical, and Carbon Dioxide Foam

Unusual Fire or Explosion Hazards: None

Fire-Fighting Instructions: Fire fighters should wear self-contained breathing apparatus. Do not release runoff from fire control methods to sewers or waterways.

Fire-Fighting Equipment: Because fire may produce toxic thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full facepiece operated in pressure-demand or positive-pressure mode.



Section 6 - Accidental Release Measures

Spill /Leak Procedures: Dike and contain spill; absorb or scrape up excess into suitable container for disposal. Stop or reduce discharge if it can be done safely.

Regulatory Requirements: Follow applicable OSHA regulations (29 CFR 1910.120).

Section 7 - Handling and Storage

Handling Precautions: Minimize breathing of vapors and avoid prolonged or repeated contact with skin. Wear proper protective equipment. If ventilation is not sufficient, wear proper respiratory equipment. Use good general housekeeping procedures.

Storage Requirements: Store in cool dry, well-ventilated area.

Section 8 - Exposure Controls / Personal Protection

Engineering Controls:

Ventilation: Provide general or local exhaust ventilation systems to maintain airborne concentrations below OSHA PELs (Sec. 2). Local exhaust ventilation is preferred because it prevents contaminant dispersion into the work area by controlling it at its source.

Administrative Controls:

Respiratory Protection: Seek professional advice prior to respirator selection and use. Follow OSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear an MSHA/NIOSH-approved respirator. Select respirator based on its suitability to provide adequate worker protection for given working conditions, level of airborne contamination, and presence of sufficient oxygen. For emergency or nonroutine operations (cleaning spills, reactor vessels, or storage tanks), wear an SCBA. *Warning! Air-purifying respirators do not protect workers in oxygen-deficient atmospheres.* If respirators are used, OSHA requires a written respiratory protection program that includes at least: medical certification, training, fit testing, periodic environmental monitoring, maintenance, inspection, cleaning, and convenient, sanitary storage areas.

Protective Clothing/Equipment: Wear chemically protective gloves, boots, and aprons to prevent prolonged or repeated skin contact. Wear protective eyeglasses or chemical safety goggles, per OSHA eye- and face-protection regulations (29 CFR 1910.133). Contact lenses are not eye protective devices. Appropriate eye protection must be worn instead of, or in conjunction with contact lenses.

Comments: Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics

Section 9 - Physical and Chemical Properties

| | |
|--|--|
| Physical State: Liquid | Water Solubility: Negligible: |
| Appearance : Clear oily liquid | Boiling Point: 370°C |
| Odor : mild odor | % Volatile: Nil |
| Vapor Pressure (mm of Hg): 8.6×10^{-6} @ 20°C | Freezing/Melting Point: None Determined |
| Vapor Density (Air=1): 10.8 | Viscosity: 1 poise |
| Specific Gravity (H₂O=1, at 4 °C): 1.12 | Evaporation Rate: None Determined |

Section 10 - Stability and Reactivity

Stability: SO-Flex is stable at room temperature in closed containers under normal storage and handling conditions.

Polymerization: Hazardous polymerization can not occur.

Chemical Incompatibilities: Strong acids and oxidizers.

Conditions to Avoid: Avoid contamination with water and other materials that react with amines.

Thermal Decomposition Products: Oxides of nitrogen, carbon monoxide and carbon dioxide

Section 11- Toxicological Information

Toxicity Data:

Acute Inhalation Effects: None established

Acute Oral Effects: None Established

Reproductive Toxicity: None Established
Mutagenicity: None Established
Teratogenicity: None Established
Sensitization: None Established

Section 12 - Ecological Information

None Established

Section 13 - Disposal Considerations

Disposal: This material contains a hazardous constituent as identified in RCRA, Title 40 CFR 261, Appendix VIII and must be disposed of in accordance with applicable Federal, state, and local regulations.

Section 14 - Transport Information

| DOT | IATA | IMDG |
|--|--|--|
| <u>55 Gallon Quantities or Greater</u> Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. Butyl Benzyl Phthalate Mixture UN #: 3082 Hazard Class: 9 Label: Miscellaneous | <u>55 Gallon Quantities or Greater</u> Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. Butyl Benzyl Phthalate Mixture UN #: 3082 Hazard Class: 9 Label: Miscellaneous | <u>All Quantities</u> Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. Butyl Benzyl Phthalate Mixture UN #: 3082 Hazard Class: 9 Label: Marine Pollutant |

Section 15 - Regulatory Information

EPA Regulations:

RCRA Hazardous Waste Number: Not listed (40 CFR 261.33)

CERCLA Hazardous Substance (40 CFR 302.4) listed per RCRA, Sec. 3001; CWA, Sec. 311 (b)(4); CWA, Sec. 307(a), CAA, Sec. 112

| <u>Components That Require Reporting</u> | <u>RQ</u> | <u>% of Reportable Component</u> |
|--|-----------|----------------------------------|
| Butyl Benzyl Phthalate | 100 lbs. | 99.7.0 Max. |
| Mercury (as part of catalyst) | 1 lb. | 0.09 Max |

This product contains the following chemicals that are subject to release reporting requirements under section 313 of SARA Title III.

| <u>Chemical Name</u> | <u>CAS #</u> | <u>% by Weight</u> |
|----------------------|--------------|--------------------|
| Mercury Compounds | - | 0.3 Max |

TSCA Inventory Status (40 CFR 710): All components of this product are listed on the TSCA inventory.

SARA EHS (Extremely Hazardous Substance) (40 CFR 355): Not listed, Threshold Planning Quantity (TPQ)

States Right To Know, Substance List:

California Proposition 65: These products contain Butyl Benzyl Phthalate and a mercury compound, which have been identified by the state of California to cause birth defects or other reproductive harm.

Delaware, Massachusetts, Minnesota, New Jersey, New York and Pennsylvania:

| <u>Chemical Name</u> | <u>CAS #</u> | <u>% by Weight</u> |
|------------------------|--------------|--------------------|
| Butyl Benzyl Phthalate | 85-68-7 | 99.7 Max |

16 - Other Information

Prepared By: Dominick J. Finocchio

Title: Technical Director

Disclaimer: The information contained in this MSDS is considered accurate as of the version date. However, no warranty is expressed or implied regarding the accuracy of the data. Since the use of this product is not within the control of Smooth-On Inc., it is the user's obligation to determine the suitability of the product for its intended application and assumes all risk and liability for its safe use.