



Material Safety Data Sheet

Sonite WAX II

MSDS No. 915A

Date Of Preparation: January 17, 2008

Revision: 0000

Section 1 - Chemical Product and Company Identification

Product/Chemical Name: Sonite WAX II

General Use: Semi-permanent Mold Release

Manufacturer: Smooth-On Inc., 2000 St. John St., Easton PA 18042

Phone (610) 252-5800, FAX (610) 252-6200

Emergency Contact: Chem-Tel

Domestic 800-255-3924

International 813-248-0585

Section 2 - Composition / Information on Ingredients

Component	CAS Number	ACGIH TWA	Exposure Limits OSHA PEL	Weight Percent (%)
Petroleum Solvent	64742-48-9	None Established	None Established	70-75
Resin Solution	Mixture	None Established	None Established	25-30

Potential Health Effects Potential Health Effects

Acute Effects Inhalation: Over exposure by inhalation of vapors may cause respiratory irritation or nonspecific discomfort such as nausea, headache or weakness. Inhalation of concentrations above the recommended limits may cause temporary central nervous system depression with anesthetic effects such as dizziness, headache, in coordination and loss of consciousness or temporary alteration of the heart's electrical activity (cardiac arrhythmia). Gross overexposure may be fatal. Inhalation of respirable aerosols of the release agent in this product may cause serious toxic effect in the lungs, based on animal studies.

Eye: Slightly irritating but does not injure eye tissue.

Skin: Frequent or prolonged contact may irritate and cause dermatitis. Skin contact may aggravate an existing dermatitis condition.

Ingestion: Ingestion is not considered a potential route of exposure

Carcinogenicity: This product contains no components listed as carcinogenic by IARC, NTP, and OSHA 1910(Z).

Medical Conditions Aggravated by Long-Term Exposure:

Individuals with preexisting diseases of the central nervous or cardiovascular system may have increased susceptibility to the toxicity of excessive exposure.

Chronic Effects: No chronic health effects known.

HMIS	
H	2
F	2
R	1

Section 4 - First Aid Measures

Inhalation: Remove source(s) of contamination and move victim to fresh air. If breathing has stopped, give artificial respiration, then oxygen if needed. Contact physician immediately.

Eye Contact: Flush eyes with plenty of water. If irritation persists, seek medical attention.

Skin Contact: In case of skin contact, wash thoroughly with soap and water.

Ingestion: Ingestion is unlikely route of exposure. Do not induce vomiting unless instructed by a physician.

Section 4 - First Aid Measures (continued)

After first aid, get appropriate in-plant, paramedic, or community medical support.

Note to Physicians: Because of possible disturbance of cardiac rhythm, catecholamine drugs, such as epinephrine, should be used only in situations of emergency life support.

Section 5 - Fire-Fighting Measures

Flash Point: 104°F (40°C)

Flammable Limits: LEL: 1.2 Note: Approximate
UEL: 9.6 Note: Approximate

Flash Point Method: TCC

Autoignition Temperature: 559° F (293° C) Note: Approximate


Flammability Classification: Flammable Liquid

Extinguishing Media: Water Fog, Dry Chemical, and Carbon Dioxide Foam

Unusual Fire or Explosion Hazards: None

Fire and Explosion Hazards: Vapors confined in a poorly ventilated area may be ignited by a spark or flame. Vapors may travel considerable distances to source of ignition. Vapors are heavier than air and may accumulate in low areas. Containers may rupture or explode under fire conditions. Hazardous decomposition products may be formed. Material can accumulate static charges, which can cause an incendiary electrical discharge. Empty containers retain product residue and can be dangerous.

Fire-Fighting Instructions: Use dry chemical, foam or CO₂; water may be ineffective but should be used to keep containers cool.



Section 6 - Accidental Release Measures

Spill /Leak Procedures: Avoid breathing vapors. Evacuate area until vapor has been dispersed. Remove all sources of ignition. Stop or reduce discharge if it can be done safely.

Section 7 - Handling and Storage

Handling Precautions: Minimize breathing of vapors and avoid prolonged or repeated contact with skin. Wear proper protective equipment. If ventilation is not sufficient, wear proper respiratory equipment. Do not use near ignition sources. Contents under pressure. Do not puncture or incinerate. Use proper grounding procedures.

Storage Requirements: Store in cool dry, well-ventilated area away from all sources of ignition. Empty container may contain residues, which are hazardous. Do not pressurize, cut, heat, or weld containers.

Section 8 - Exposure Controls / Personal Protection

Engineering Controls:

Ventilation: Provide general or local exhaust ventilation systems to maintain airborne concentrations below OSHA PELs (Sec. 2). Local exhaust ventilation is preferred because it prevents contaminant dispersion into the work area by controlling it at its source.

Administrative Controls:

Respiratory Protection: Seek professional advice prior to respirator selection and use. Follow OSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear an MSHA/NIOSH-approved respirator.

Section 8 - Exposure Controls / Personal Protection

Select respirator based on its suitability to provide adequate worker protection for given working conditions, level of airborne contamination, and presence of sufficient oxygen.

For emergency or nonroutine operations (cleaning spills, reactor vessels, or storage tanks), wear an SCBA. *Warning! Air-purifying respirators do not protect workers in oxygen-deficient atmospheres.* If respirators are used, OSHA requires a written respiratory protection program that includes at least: medical certification, training, fit testing, periodic environmental monitoring, maintenance, inspection, cleaning, and convenient, sanitary storage areas.

Protective Clothing/Equipment: Wear chemically protective gloves, boots, aprons, and gauntlets to prevent prolonged or repeated skin contact. Wear protective eyeglasses or chemical safety goggles, per OSHA eye- and face-protection regulations (29 CFR 1910.133). Contact lenses are not eye protective devices. Appropriate eye protection must be worn instead of, or in conjunction with contact lenses.

Safety Stations: Make emergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area.

Contaminated Equipment: Separate contaminated work clothes from street clothes. Launder before reuse. Remove this material from your shoes and clean personal protective equipment.

Comments: Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics.

Section 9 - Physical and Chemical Properties

Product Form: Soft Paste	Water Solubility: Insoluble
Appearance and Odor: Yellow, Slight ethereal odor	Boiling Point: >311°F (155C)
Specific Gravity: 0.78	Evaporation Rate (BuAc=1): 0.04
Volatile Organic Content (grams/liter): 571	Vapor Pressure: None Established
	Vapor Density (Air=1): None Established

Section 10 - Stability and Reactivity

Stability: This product is stable at room temperature.

Polymerization: Hazardous polymerization cannot occur.

Hazardous Decomposition Products: Thermal oxidative decomposition can produce; carbon monoxide, carbon dioxide and hydrocarbons.

Section 11- Toxicological Information

None Established

Section 12 - Ecological Information

None Established

Section 13 - Disposal Considerations

Disposal: Contact your supplier or a licensed contractor for detailed recommendations. Follow applicable federal, state, and local regulations.

Section 14 - Transport Information

DOT	IATA	IMDG
Not Regulated In Containers of 119 Gallons Capacity or Less	Shipping Name: Petroleum Distillate N.O.S. (Naphtha Solvent) UN #: 1268 Hazard Class: 3 Packing Group: III	Shipping Name: Petroleum Distillate N.O.S. (Naphtha Solvent) UN #: 1268 Hazard Class: 3 Packing Group: III

Section 15 - Regulatory Information

EPA Regulations:

SARA Toxic Chemical (40 CFR 372.65): None

SARA EHS (Extremely Hazardous Substance) (40 CFR 355): None

TSCA Inventory Status (40 CFR 710): All components of this formulation are listed in the TSCA Inventory.

Section 15 - Regulatory Information (continued)

States Right To Know, Substance List:

California Proposition 65: This product does not intentionally contain any chemicals which have been identified by the state of California to cause cancer, birth defects or other reproductive harm.

Section 16 - Other Information

Prepared By: Dominick J. Finocchio

Title: Technical Director

The information contained in this MSDS is considered accurate as of the version date. However, no warranty is expressed or implied regarding the accuracy of the data. Since the use of this product is not within the control of Smooth-On Inc., it is the user's obligation to determine the suitability of the product for its intended application and assumes all risk and liability for its safe use.